



TECHNICAL DATA SHEET

Type no.	50 300
Article no.	010503000101
Standards	DIN EN 50342, DIN IEC 60095-2
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	69 Ah (K20)
Cold start current	520 A (EN)
Dimensions and weights	
Box	H5
Length max.	241mm
Width max.	175mm
Box height max.	190mm
Total height max.	190mm
Battery weight	Ca. 15,5 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	72
Pallet ID	Euro palett
Items per layer	18
Features	
Base hold-down	B1 + B13
Layout	0+1
Terminal	1+19
Separator	PE bag separator
Degassing	Battery with single degassing
Flame arrester	Available
Maintenance ¹⁾	
Water consumption	< 1g/Ah
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,8 V



Symbolpicture

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge

Document DBTBAT00259 prepared on 2013-09-19 ; Rights relating to changes and errors retained.
original