

TECHNICAL DATA SHEET



Type no.	650 11
Article no.	010650110101
Standards	DIN EN 50342-1, 50342-4
Application	Starter battery, high cranking current application
Electrical data	
Rated voltage	12V
Rated capacity	150 Ah (K20)
Cold start current	1150 A (EN)
Dimensions and weights	
Box	A
Length max.	514mm
Width max.	189mm
Box height max.	195mm
Total height max.	220mm
Battery weight	Ca. 39,0 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	24
Pallet ID	Euro pallet
Items per layer	8
Features	
Base hold-down	B00
Layout	3
Terminal	1
Separator	PE bag separator
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - V3 - E2
Maintenance 1)	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage 2)	max. 14,8 V



1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01; Rights relating to changes and errors retained.
original