




TECHNICAL DATA SHEET

Type no.	960 51	
Article no.	010960510101	
Standards	DIN EN 50342, DIN IEC 60095-2	
Application	Long-term discharge battery	
Electrical data		
Rated voltage	12V	
Rated capacity	105 Ah (K5)	
Cold start current		
Dimensions and weights		
Box	A	
Length max.	514mm	
Width max.	189mm	
Box height max.	195mm	
Total height max.	220mm	
Battery weight	Ca. 37,5 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	24	
Pallet ID	Euro palett	
Items per layer	8	
Features		
Base hold-down	B00	
Layout	3	
Terminal	1	
Separator	PE bag separator with glass nonwoven	
Degassing	Battery with single degassing	
Flame arrester	Available	
Maintenance 1)		
Water consumption	> 4g/Ah	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 9 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 13,8 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

Document DBTBAT00285 prepared on 2013-09-19 ; Rights relating to changes and errors retained.
original