

TECHNICAL DATASHEET

Printed: 07/11/2011 Product Management

TECHNOLOGIES					Transportation Europe	
	Code: G31072A08 ther: 31M700BXL			Created: Modified:	08/06/2010 21/09/2010	
r			Fi	inal Outlook G31 pproval date 15/06		
(159 (159,65)	3.00 [330	223 (1,0)] 223 (1,0)]	(.855 (2),72) (1),72) (1),72)			
			9,395, ¹⁰⁰ [238,43, ⁰ ,27]	6.376 ^{+,000} [162,00, ¹ ,01]	9.299 ^{+,005} [235,9 ^{+,0} ,27]	
PERFORMANCES			CONTAINER			
Voltage (V):	12 V		Туре:	G31	BLACK	
C20 (Ah):	100.0	20 h	Hold Down:	B0		
Rc (min):	200		H. D. Adapter:	No		
Cranking (A):	king (A): 720 EN COVER					
Vibration:	V3 (35Hz/6g/20)h)	Туре:	Flat/Press	BLUE LIGHT	
Endurance:	500 cycles@75	5%	Polarity:	ETN 1	2202 2.0111	
Charge:	CHARGED		Terminals:	SAE M 3/8"- 5/	16" taper&stud	
Technology:	AGM		Terminal Adapter:	No		
Grid :	Ca/Ca		SOCI:	No		
WEIGHT AND STD. DIMENSIONS			Ventilation:	Independent		
			Filter:	No		
Battery Weight ((kg): 31.84		Lateral Plug:	No		
Volume acid (I): 0.00			PLUGS			
Length (mm): 330			Type: 6 x M	118 Valve	GREY MEDIUM	
Width (mm): 173			HANDLES			
Height (mm): 240			Type: 1 x S		BLACK	
				OTHERS	-	
			Degassing Tube:	No		
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations			3/8-5/16 nuts in pla	3/8-5/16 nuts in plastic bag		
ENSUS42 and applicable European Regulations			3/8-5/16 nuts in plastic bag			

EN50342 and applicable European Regulations 3/8-5/16 nuts in plastic bag

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.