




# TECHNICAL DATA SHEET

Type no.	<b>P45 24</b>	
Article no.	013545240101	
Standards	DIN EN 50342, DIN IEC 60095-2	
Application	Starter battery	
<b>Electrical data</b>		
Rated voltage	12V	
Rated capacity	45 Ah (K20)	
Cold start current	360 A (EN)	
<b>Dimensions and weights</b>		
Box	45NS	
Length max.	238mm	
Width max.	129mm	
Box height max.	203mm	
Total height max.	225mm	
Battery weight	Ca. 12,0 kg (+/- 5 %)	Symbolpicture
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	81	
Pallet ID	Euro palett	
Items per layer	27	
<b>Features</b>		
Base hold-down	B00	
Layout	1	
Terminal	1+3	
Separator	PE bag separator	
Degassing	Battery with central degassing	
Flame arrester	Available	
<b>Maintenance 1)</b>		
Water consumption	< 1g/Ah	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 3 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 14,8 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

Document DBTBAT00266 prepared on 2013-09-19 ; Rights relating to changes and errors retained.  
original